



COMBINATION LOCK INSTRUCTIONS

To set your personal combination:

1. Dial 0-0-0-0 on the indication line, then pull up the shackle.
2. Turn the shackle 180°, then press the shackle down and set the 4-point combination lock to your private code, turning each dial until the desired digits are on the indication line.
3. Pull up the shackle and return to the original position.
4. Your new private code is now set.

Always remember your code and keep it in a secure place from others.

To change your code, follow steps 1-4, using your new private code at step 1.

Cleaning:

Over time, dust, particles and chemicals in the air can create friction inside the locks' components hindering the performance of the lock.

We recommended cleaning and lubrication every 3-6 months to keep your lock operating like new. If you are using your lock outdoors, or in a dusty/corrosive environment, you should follow this process every 3 months.

1. To clean the lock, use pressurized air to blow all dust out of the dial and shackle openings.
2. Lubricate your lock using an all-purpose oil or lubrication spray, but **AVOID** using dry graphite, or a silicone lubricant as these can cause damage to your lock.
3. Apply lubricant sparingly. All you will need is a very light spray(aerosol), or a few drops(oil). Lubricate both the dials and the shackle.
4. Allow lubricant to drain into the lock. You can tap the lock on a table to help distribute the lubricant inside the lock.
5. After application, turn the dials and open and close the lock several times to distribute the lubricant. Wipe excess lubricant off the lock, shackle and dials using a microfiber cloth and let the lock air dry. Once dry, it's ready to use again.